


A Temporal Knowledge Graph for Music Festival Lineup Forecasting

Task: forecast festival lineups as link prediction in a temporal knowledge graph (TKG): Which artists will perform a festival next year, and at which festival will an artist perform?

Contributions:

- A TKG of 380 festivals over 55 years, from Setlist.fm and MusicBrainz
- Lineup forecasting as a use-case-driven task with suitable metrics
- Evaluation of six TKG forecasting methods and four zero-shot LLMs



1 Motivation: Why Forecast Lineups?

Fans & organizers

Festival passes are cheapest before the lineup is announced, and fans plan their summer around their favorite bands.

Who will perform at Southside Festival 2027?
(?, performsAt, SouthsideFestival, 2027)

Where will Arlo Parks perform in 2027?
(ArloParks, performsAt, ?, 2027)

Need: future artist-festival links

TKG forecasting research

- Benchmarks (ICEWS, Polecat, GDEL, YAGO, Wikidata) score generic link prediction aggregated over all relations
- Hard to interpret from an application perspective



Need: use-case-grounded benchmarks

Can we forecast future lineups from historical data with TKG forecasting?

2 Dataset: A TKG of German Festivals

- **Sources:** Setlist.fm (concerts, venues, festivals) + MusicBrainz (artist origin, type, releases, genres, labels), joined via shared artist IDs
- **Scope:** 380 German festivals held ≥ 5 times with ≥ 30 artists, 1971–2025, yearly, e.g. (Arlo Parks, performsAtFestival, Melt!, 2022)
- **Schema:** 23 relations: performances, releases, artist metadata, labels
- **Two Variants** with identical test queries: `concert` (all relations), `concertp` (only `performsAtFestival`)

	Domain	Relation	Range
Performance Information	ARTIST	performs at festival	FESTIVAL
	FESTIVAL	happens in venue	VENUE
	ARTIST	performs concert at	VENUE
Release Information	ARTIST	releases album	RELEASE
	ARTIST	releases EP	RELEASE
Meta Data	ARTIST	has begin area	AREA
	ARTIST	has type	AREA
Label Relationships	ARTIST	label founder	LABEL
	ARTIST	recording contract	LABEL
	ARTIST	personal label	LABEL
	ARTIST	artists and repertoire position at	LABEL
	ARTIST	personal publisher	LABEL
	ARTIST	owner	LABEL
	ARTIST	producer position at	LABEL
	ARTIST	creative position at	LABEL
	ARTIST	executive position at	LABEL
	ARTIST	engineer position at	LABEL
	ARTIST	named after label	LABEL
	ARTIST	named after artist	LABEL



Only 2.9% of 2025 lineup facts recur from 2024 (contrast: YAGO: 92.7%):
Re-predicting same lineup as previous year is thus not promising.

3 Task & Evaluation

Single-step forecasting of `performsAtFestival` for 2025, in two directions:

- **Artist prediction** (?, performsAtFestival, Y, 2025)
- **Festival prediction** (X, performsAtFestival, ?, 2025)

Why time-aware filtered MRR misleads here

Example: A festival with 100 artists; the model ranks a correct artist at every odd position (1, 3, ..., 199), a wrong one at every even position.



Time-aware filtered MRR
(1 + 1/2 + ... + 1/100) / 100 = 5.2%

-> Every second prediction correct, yet MRR only 5.2%.

A festival query can have over 200 correct answers.

Additional Metrics:

- **R-Precision (PR):** correct share of the top R_i predictions, R_i = number of true answers
- **Normalized 10-Precision (PN10):** correct among the top 10, divided by $\min(R_i, 10)$

PR = 50/100 = 50%
PN10 = 5/10 = 50%

4 Compared Methods

6 TKG forecasting methods

- Rule-based: CountTRuCoLa, TLogic
- GNN + RNN: RE-GCN, CEN
- Path-based: CognTKE
- Recurrency Baseline

4 zero-shot LLMs, no TKG access*

- Llama 3.1 8B / 3.3 70B, Mixtral 8x7B, GPT-4o-mini
- knowledge cutoff $\leq$ late 2023
- free-text names are mapped back to TKG nodes

* Question: can broadly accessible, general-purpose LLMs compete with specialized TKG forecasting methods?

5 Results: PN10 (%)

Predicting artists for a festival

CognTKE	11.9
CountTRuCoLa	10.2
Recurrency Baseline	9.4
RE-GCN	6.5
CEN	5.8
TLogic	3.3
Llama 3.3 70B	1.7
GPT-4o-mini	0.7
Mixtral 8x7B	0.6
Llama 3.1 8B	0.5

-> hard: too low for standalone use

Predicting festivals for an artist

CountTRuCoLa	41.4
CognTKE	34.4
CEN	33.5
Recurrency Baseline	31.9
RE-GCN	30.5
TLogic	21.5
Llama 3.3 70B	17.2
Mixtral 8x7B	15.9
GPT-4o-mini	14.2
Llama 3.1 8B	10.2

-> usable as a ranked shortlist

TKG methods, trained on `concertp` zero-shot LLMs, no TKG. MRR, Hits@k, PR: see paper.

6 What We Learned

Findings on LLM Predictions

- **Popularity bias:** GPT-4o-mini ranks Billie Eilish top-3 for 47.1% of queries, though she played no German festival in 2025
- **Duplicates:** Llama 3.1 8B repeats Robin Schulz 23x per list on average
- **Autoregressive effects:** consecutive predictions share properties such as gender or genre

1. Saxon	21. Turisas
2. Judas Priest	22. Sabaton
3. Iron Maiden	23. Amon Amarth
4. Scorpions	24. Children of Bodom
5. Helloween	25. In Flame s
6. Blind Guardian	26. Dark Tranquillity
7. Accept	27. At the Gates
8. U.D.O.	28. Arch Enemy
9. Sabaton	29. Nightwish
10. Powerwolf	30. Epica
11. Rhapsody of Fire	31. Within Temptation
12. Hammerfall	32. Delain
13. Stratovarius	33. Leaves' Eyes
14. Sonata Arctica	34. Xandria
15. Dragonforce	35. Lacuna Coil
16. Alestorm	36. Evanescence
17. Korpiklaani	37. Kamelot
18. Eluveitie	38. Symphony X
19. Ensiferum	39. Evergrey
20. Finntroll	40. Threshold

Llama 3.3 70B for Keep It True Festival 2025: female(-fronted) acts in green; ranks 28–36 are all green.

TKG methods

- CountTRuCoLa can only learn rules of length 1, **no multi-hop dependencies**
 - Still learns plausible rules, e.g.
 - performs at Mayfair Ballroom -> plays at Rock am Ring
 - contract with Spinefarm Records -> plays at Wacken Open Air
- TLogic cannot learn **constants** in rules
 - Substantially below the other TKG methods, although competitive on standard benchmarks
- Embedding-based Methods have **out-of-memory errors** on `concert`
 - RE-GCN and CEN underperform Recurrency Baseline
 - CognTKE competitive even when trained only on `concertp` -> research into **scalability** worthwhile direction
- **Accuracy grows with artist/festival activity;** for rare entities all methods $\approx$ baseline

Relations beyond festival performances

- Additional relations (`concert`) change PR/PN10 by at most one point
- RE-GCN, CEN and CognTKE run out of memory
- Slight gains for artist prediction, no consistent pattern for festival prediction
- Enriched data helps in some cases; also adds noise that current models struggle to cope with

Limitations

- Potential coverage gaps in crowdsourced sources (a sample checked against official festival websites showed no major omission)
- Festivals in Germany only; a global TKG would exceed what current models can process
 - Script provided to mine other countries/continents

Future Work

- More scalable TKG models for large real-world event data
- Other realistic queries: partial lineups (remaining performers) & partial schedules (additional bookings)

Paper:



Julia Gastinger, Thilo Dieing, Christian Meilicke, Heiner Stuckenschmidt

University of Mannheim · first.last@uni-mannheim.de · AKBC 2026

Code: github.com/JuliaGast/festival-lineup-tkg · Data: madata.bib.uni-mannheim.de/822 · Paper: arxiv.org/abs/2609.24467

GitHub:

